

SET-UP EXAMPLE FOR PRESSURE TANK FOR SPARKLING WINE FS-MO-8B

Item	Order No.
	<p>Stainless steel pressure tank FS-MO-140-8B-5200 litres</p> <ul style="list-style-type: none"> › h1 = 4,172 mm, $H_{ges} = 4,172 \text{ mm (h1)} + 150 \text{ mm (cleaning pipe)}$ + approx. 100 mm (height compensation) = 4,422 mm › Standard equipment as on page 123 <p style="text-align: right;">FS-MO-140-5200-8B</p>
	<p>Sampling (page 176)</p> <ul style="list-style-type: none"> › With sampling tap NW 20 DIN 11851 <p style="text-align: right;">65583</p>
	<p>Racking outlet (page 172)</p> <ul style="list-style-type: none"> › Welded gland with thread NW 50 DIN 11851 › With bevel seat valve NW 50 DIN 11851 on request <p style="text-align: right;">KA-120D 80738</p>
	<p>Bottom outlet (page 172)</p> <ul style="list-style-type: none"> › With disc valve NW 50 DIN 11851 <p style="text-align: right;">64945</p>
	<p>Cleaning pipe (page 186)</p> <ul style="list-style-type: none"> › Removable cleaning spray head NW 40, H = + 150 mm › Perforation 360° with clip fastener › Including spray head holder with cleaning pipe pulled down to operating height <p style="text-align: right;">RL-40A</p>
	<p>Pipes (page 186)</p> <ul style="list-style-type: none"> › Ventilation pipe: stainless steel pipeline NW 25 pulled down to operating height, connection NW 25 DIN 11851 › Safety fittings consisting of pressure manometer, spring-loaded safety valve, nitrogen transfer and bevel seat valve DN 25 DIN 11851 <p style="text-align: right;">EL-100A SA-100A</p>
	<p>Heating and cooling jacket (page 128)</p> <ul style="list-style-type: none"> › Double jacket B 4,1 m² with welded gland thread G 1" for the connection to available warm water / cold water source › Version 1, layout 78, connection position A1 <p style="text-align: right;">1A1</p>
	<p>Temperature measurement (page 180)</p> <ul style="list-style-type: none"> › Bi-metal dial thermometer ø 100 mm, measuring range -20 °C to +60 °C › Length = 125 mm › Including welded-on sleeve for thermometer <p style="text-align: right;">TM-140F</p>
	<p>Fill level (page 177)</p> <ul style="list-style-type: none"> › Mounted fill level indicator NW 10 DIN 11851 with litre scale › Closed version – connection between fill level indicator and cleaning pipe <p style="text-align: right;">FS-130I</p>
	<p>Adjustable feet (page 184)</p> <ul style="list-style-type: none"> › With adjustable feet for tank legs (H = + approx. 100 mm) <p style="text-align: right;">46125</p>
	<p>TÜV-fees (fees for German Technical Control Board) including technical approval and documentation</p> <p style="text-align: right;">TÜV-001</p>