












SET-UP EXAMPLE FOR FERMENTATION AND STORAGE TANK FS-MO

Item	Order No.
 <p>Base tank FS-MO-240-20000 litres</p> <ul style="list-style-type: none"> › $h_1 = 5,270 \text{ mm}$, $H_{\text{ges}} = 5,270 \text{ mm (h}_1) + 320 \text{ mm (dome)} + 150 \text{ mm (cleaning pipe)}$ + approx. 100 mm (height compensation) = 5,840 mm › Standard equipment as on page 39 	FS-MO-240-20000
 <p>Ventilation / Filling (page 138)</p> <ul style="list-style-type: none"> › Filler neck NW 400 in tank top, positioned in upright, forward direction (with welded-on bead), $H = + 320 \text{ mm}$ › Flap lid with filler neck NW 50 external thread Rd 78 x 1/6" 	OB-040T
 <p>Cleaning (page 155)</p> <ul style="list-style-type: none"> › 360° cleaning spray head perforation with clip fastener including cleaning pipe with thread NW 40 DIN 11851, $H = + 150 \text{ mm}$ › Spray head NW 40 detachable from outside › Disc valve NW 40 DIN 11851 	RL-40B RL-41A 61375
 <p>Sampling (page 146)</p> <ul style="list-style-type: none"> › With sampling tap NW 10 DIN 11851 	64949
 <p>Racking outlet (page 142)</p> <ul style="list-style-type: none"> › Welded gland with thread NW 50 DIN 11851 › With disc valve NW 50 DIN 11851 	KA-120D 64945
 <p>Fill level (page 148)</p> <ul style="list-style-type: none"> › Fill level indicator NW 10 mounted 	FS-130K
 <p>Bottom outlet (page 142)</p> <ul style="list-style-type: none"> › With disc valve NW 50 DIN 11851 	64945
 <p>Temperature measurement (page 150)</p> <ul style="list-style-type: none"> › Bi-metal dial thermometer $\varnothing 100 \text{ mm}$, measuring range $-20 \text{ }^\circ\text{C}$ to $+60 \text{ }^\circ\text{C}$ › Threaded sleeve with locking screw and cap nut NW 10 DIN 11851 	TM-140C
 <p>Heating and cooling jacket (page 100)</p> <ul style="list-style-type: none"> › Doppelmantel B7 12,9 m² mit Anschluss-Gewindestutzen AGG 1" für Anschluss an bauseits vorhandene Warm- / Kaltwasserquelle › Ausführung 1, Layout 35, Stutzenposition B7 	1B7
 <p>Stirring device (page 157)</p> <ul style="list-style-type: none"> › Stirring device flange mounted on the side of the tank shell DN 200 › Stirring device for mixing 	FL-200A
 <p>Adjustable feet (page 153)</p> <ul style="list-style-type: none"> › With adjustable feet for tank legs ($H = + \text{approx. } 100 \text{ mm}$) 	46129