












SET-UP EXAMPLE FOR FERMENTATION AND STORAGE TANK FS-MO

	Item	Order No.
	Base tank FS-MO-240-20000 litres	
	<ul style="list-style-type: none"> › h1 = 5,270 mm, $H_{ges} = 5,270 \text{ mm (h1)} + 320 \text{ mm (dome)} + 150 \text{ mm (cleaning pipe)}$ + approx. 100 mm (height compensation) = 5,840 mm › Standard equipment as on page 39 	FS-MO-240-20000
	Ventilation / Filling (page 168)	
	<ul style="list-style-type: none"> › Filler neck NW 400 in tank top, positioned in upright, forward direction (with welded-on bead), H = + 320 mm › Flap lid with filler neck NW 50 external thread Rd 78 x 1/6" 	OB-040T
	Cleaning (page 186)	
	<ul style="list-style-type: none"> › 360° cleaning spray head perforation with clip fastener including cleaning pipe with thread NW 40 DIN 11851, H = + 150 mm › Spray head NW 40 detachable from outside › Disc valve NW 40 DIN 11851 	RL-40B RL-41A 61375
	Sampling (page 176)	
	› With sampling tap NW 10 DIN 11851	64949
	Racking outlet (page 172)	
	<ul style="list-style-type: none"> › Welded gland with thread NW 50 DIN 11851 › With disc valve NW 50 DIN 11851 	KA-120D 64945
	Fill level (page 177)	
	› Fill level indicator NW 10 mounted	FS-130K
	Bottom outlet (page 172)	
	› With disc valve NW 50 DIN 11851	64945
	Temperature measurement (page 180)	
	<ul style="list-style-type: none"> › Bi-metal dial thermometer ø 100 mm, measuring range - 20 °C to + 60 °C › Threaded sleeve with locking screw and cap nut NW 10 DIN 11851 	TM-140C
	Heating and cooling jacket (page 128)	
	<ul style="list-style-type: none"> › Double jacket B7 12,9 m² with welded gland thread G 1" for connection to available warm water / cold water source › Version 1, layout 35, connection position B7 	1B7
	Stirring device (page 190)	
	<ul style="list-style-type: none"> › Stirring device flange mounted on the side of the tank shell DN200 › Stirring device for mixing 	FL-200A
	Adjustable feet (page 184)	
	› With adjustable feet for tank legs (H = + approx. 100 mm)	46129