











SET-UP EXAMPLE FOR FERMENTATION AND STORAGE TANK FS-MO

Item	Order No.	
	Base tank FS-MO-240-20000 litres	FS-MO-240-20000
<ul style="list-style-type: none"> › h1 = 5,270 mm, $H_{ges} = 5,270 \text{ mm (h1)} + 320 \text{ mm (dome)} + 150 \text{ mm (cleaning pipe)}$ + approx. 100 mm (height compensation) = 5,840 mm › Standard equipment as on page 35 		
	Ventilation / Filling (page 172)	OB-040T
<ul style="list-style-type: none"> › Filler neck NW 400 in tank top, positioned in upright, forward direction (with welded-on bead), H = + 320 mm › Flap lid with filler neck NW 50 external thread Rd 78 x 1/6" 		
	Cleaning (page 188)	RL-40B
<ul style="list-style-type: none"> › 360° cleaning spray head perforation with clip fastener including cleaning pipe with thread NW 40 DIN 11851, H = + 150 mm › Spray head NW 40 detachable from outside › Disc valve NW 40 DIN 11851 		RL-41A
	Sampling (page 179)	64949
<ul style="list-style-type: none"> › With sampling tap NW 10 DIN 11851 		
	Racking outlet (page 175)	KA-120D
<ul style="list-style-type: none"> › Welded gland with thread NW 50 DIN 11851 › With disc valve NW 50 DIN 11851 		64945
	Fill level (page 180)	FS-130K
<ul style="list-style-type: none"> › Fill level indicator NW 10 mounted 		
	Bottom outlet (page 175)	64945
<ul style="list-style-type: none"> › With disc valve NW 50 DIN 11851 		
	Temperature measurement (page 182)	TM-140C
<ul style="list-style-type: none"> › Bi-metal dial thermometer ø 100 mm, measuring range - 20 °C to + 60 °C › Threaded sleeve with locking screw and cap nut NW 10 DIN 11851 		
	Heating and cooling jacket (page 130)	1B7
<ul style="list-style-type: none"> › Double jacket B7 12,9 m² with welded gland thread G 1" for connection to available warm water / cold water source › Version 1, layout 35, connection position B7 		
	Adjustable feet (page 186)	46129
<ul style="list-style-type: none"> › With adjustable feet for tank legs (H = + approx. 100 mm) 		