










SET-UP EXAMPLE FOR FERMENTATION AND STORAGE TANK FS-MO

Item	Order No.
	<p>Base tank FS-MO-240-20000 liter</p> <ul style="list-style-type: none"> · h1 = 5,270 mm, · $H_{\text{compl.}} = 5,270 \text{ mm (h1)} + 320 \text{ mm (dome)} + 150 \text{ mm (cleaning pipe)}$ · + approx. 100 mm (height compensation) = 5,840 mm · Standard equipment as on page 35 <p style="text-align: right;">FS-MO-240-20000</p>
	<p>Ventilation / Filling (page 138)</p> <ul style="list-style-type: none"> · Filler neck NW 400 in tank top, positioned in upright, forward direction (with welded-on bead), H = + 320 mm · Flap lid with filler neck NW 50 external thread Rd 78 x 1/6" <p style="text-align: right;">OB-040T</p>
	<p>Cleaning (page 154)</p> <ul style="list-style-type: none"> · 360° cleaning spray head perforation with clip fastener including cleaning pipe with thread NW 40 DIN 11851, H = + 150 mm · Spray head NW 40 detachable from outside · Disc valve NW 40 DIN 11851 <p style="text-align: right;">RL-040C RL-041A 61375</p>
	<p>Sampling (page 145)</p> <ul style="list-style-type: none"> · With sampling tap NW 10 DIN 11851 <p style="text-align: right;">64949</p>
	<p>Racking outlet (page 140)</p> <ul style="list-style-type: none"> · Welded gland NW 50 DIN 11851 · With disc valve NW 50 DIN 11851 <p style="text-align: right;">KA-120D 64945</p>
	<p>Fill level (page 146)</p> <ul style="list-style-type: none"> · Fill level indicator NW 10 mounted <p style="text-align: right;">FS-130K</p>
	<p>Bottom outlet (page 140)</p> <ul style="list-style-type: none"> · With disc valve NW 50 DIN 11851 <p style="text-align: right;">64945</p>
	<p>Temperature measurement (page 148)</p> <ul style="list-style-type: none"> · Bi-metal dial thermometer ø 100 mm, measuring range - 20 °C bis + 60 °C · Threaded sleeve with locking screw and cap nut NW 10 DIN 11851 <p style="text-align: right;">TM-140C</p>
	<p>Cooling and heating (page 98)</p> <ul style="list-style-type: none"> · Double jacket B7 12.9 m² with welded gland thread G 1" for connection to available warm water / cold water source · Version 1, layout 75, connection position B7 <p style="text-align: right;">1B7</p>
	<p>Adjustable feet (page 152)</p> <ul style="list-style-type: none"> · With adjustable feet for tank legs (H = + approx. 100 mm) <p style="text-align: right;">46129</p>