

SET-UP EXAMPLE FOR MULTI-COMPARTMENT TANK MS-MO

Item

Order No.



FS-MO base tank FS-MO-120-2000 litres

› $h_1 = 2,173$ mm,

$H_{ges} = 2,173$ mm (h_1) + 80 mm (connection) + 100 mm (height compensation) = approx. 2,353 mm

› Standard equipment as on page 55

FS-MO-120-2000

Multiple-compartment tank

› Upper tank compartment 1,000 litres

› Lower tank compartment 1,000 litres

MS-MO-120-S

Equipment for each tank compartment:



Sampling (page 139)

› With sampling tap NW 10 DIN 11851

2x 64949



Racking outlet (page 135)

› With mounted flap valve Gr. 37

2x KA-120I



Fill level (page 140)

› Mounted fill level indicator NW 10

2x FS-130H



Bottom outlet (page 135)

› With disc valve NW 50 DIN 11851

2x 64945



Temperature measurement (page 142)

› Bi-metal dial thermometer \varnothing 100 mm, measuring range -20°C to $+60^{\circ}\text{C}$

› Threaded sleeve with locking screw and cap nut NW 10 DIN 11851

2x TM-140C



Cooling and heating jacket lower tank compartment (page 98)

› Double jacket shape A2 $1,3\text{ m}^2$ with welded gland thread G 1" for connection to available warm water / cold water source

› Version 1, layout 15, connection position A2

1A2



Cooling and heating jacket upper tank compartment (page 98)

› Double jacket shape A2 $1,3\text{ m}^2$ with welded gland thread G 1" for connection to available warm water / cold water source

› Version 1, layout 15, connection position A2

1A2

Equipment per tank:



Adjustable feet (page 145)

› With adjustable feet for tank legs ($H = +$ approx. 100 mm)

46127