











SET-UP EXAMPLE FOR RECTANGULAR BASE TANK RS-MO / STACKING TANK RA-MO

	Item	Order No.
	<p>Rectangular base tank RS-MO-110-2300 litres</p> <p>› h1 = approx. 1,797 mm</p> <p>› Standard equipment as on page 49</p>	RS-MO-110-2300
	<p>Rectangular stacking tank RA-MO-110-2300 litres</p> <p>› h5 = 1,548 mm, H = 1,797 mm (h1) + 70 mm (h4) + 1,548 mm (h5) = 3,415 mm,</p> <p>$H_{ges} = 3,415 \text{ mm (H)} + 80 \text{ mm (connection)} + \text{approx. } 100 \text{ mm (height compensation)}$</p> <p>= approx 3,595 mm</p> <p>› Standard equipment as on page 49</p>	RA-MO-110-2300
	<p>Sampling (page 146)</p> <p>› With sampling tap NW 10 DIN 11851</p>	2x 64949
	<p>Racking outlet (page 142)</p> <p>› Welded gland with thread NW 50 DIN 1185</p> <p>› With disc valve NW 50 DIN 11851</p>	2x KA-120D 2x 64945
	<p>Fill level (page 148)</p> <p>› Fill level indicator NW 10 mounted</p>	2x FS-130H
	<p>Bottom outlet (page 142)</p> <p>› With yeast plug</p> <p>› With disc valve NW 50 DIN 11851</p>	2x HS-100A 2x 64945
	<p>Temperature measurement (page 150)</p> <p>› Bi-metal dial thermometer \varnothing 100 mm, measuring range -20 °C to +60 °C</p> <p>› Threaded sleeve with locking screw and cap nut NW 10 DIN 11851</p>	2x TM-140C
	<p>Heating and cooling jacket for base tank (page 100)</p> <p>› Double jacket C5 1,3 m² with welded gland G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>	1C5
	<p>Heating and cooling jacket for stacking tank (page 100)</p> <p>› Double jacket C5 1,3 m² with welded gland G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>	1C5
	<p>Adjustable feet (page 153)</p> <p>› With adjustable feet for tank legs (H = + approx. 100 mm)</p>	46126