











SET-UP EXAMPLE FOR RECTANGULAR BASE TANK RS-MO / STACKING TANK RA-MO

	Item	Order No.
	<p>Rectangular base tank RS-MO-110-2300 litres</p> <p>› h1 = approx. 1,797 mm</p> <p>› Standard equipment as on page 45</p>	RS-MO-110-2300
	<p>Rectangular stacking tank RA-MO-110-2300 litres</p> <p>› h5 = 1,548 mm, H = 1,797 mm (h1) + 70 mm (h4) + 1,548 mm (h5) = 3,415 mm,</p> <p>$H_{ges} = 3,415 \text{ mm (H)} + 80 \text{ mm (connection)} + \text{approx. } 100 \text{ mm (height compensation)} = 3,595 \text{ mm}$</p> <p>› Standard equipment as on page 45</p>	RA-MO-110-2300
	<p>Sampling (page 143)</p> <p>› With sampling tap NW 10 DIN 11851</p>	2x 64949
	<p>Racking outlet (page 139)</p> <p>› With mounted flap valve Gr. 37</p>	2x KA-120I
	<p>Fill level (page 144)</p> <p>› Mounted fill level indicator NW 10</p>	2x FS-130H
	<p>Bottom outlet (page 139)</p> <p>› With disc valve NW 50 DIN 11851</p>	2x 64945
	<p>Temperature measurement (page 146)</p> <p>› Bi-metal dial thermometer \varnothing 100 mm, measuring range - 20 °C to + 60 °C</p> <p>› Threaded sleeve with locking screw and cap nut NW 10 DIN 11851</p>	2x TM-140C
	<p>Cooling and heating jacket for base tank (page 98)</p> <p>› Double jacket C5 1,3 m² with welded gland thread G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>	1C5
	<p>Cooling and heating jacket for stacking tank (page 98)</p> <p>› Double jacket C5 1,3 m² with welded gland thread G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>	1C5
	<p>Adjustable feet (page 149)</p> <p>› With adjustable feet for tank legs (H = + approx. 100 mm)</p>	46126