











**SET-UP EXAMPLE FOR RECTANGULAR BASE TANK RS-MO / STACKING TANK RA-MO**

|   | Item  | Order No.              |
|---|---|------------------------|
|    | <p><b>Rectangular base tank RS-MO-110-2300 litres</b></p> <p>› h1 = approx. 1,797 mm</p> <p>› Standard equipment as on page 49</p>  | RS-MO-110-2300         |
|    | <p><b>Rectangular stacking tank RA-MO-110-2300 litres</b></p> <p>› h5 = 1,548 mm, H = 1,797 mm (h1) + 70 mm (h4) + 1,548 mm (h5) = 3,415 mm,</p> <p><math>H_{ges} = 3,415 \text{ mm (H)} + 80 \text{ mm (connection)} + \text{approx. } 100 \text{ mm (height compensation)}</math></p> <p>= approx. 3,595 mm</p> <p>› Standard equipment as on page 49</p> | RA-MO-110-2300         |
|    | <p><b>Sampling (page 176)</b></p> <p>› With sampling tap NW 10 DIN 11851</p>  | 2x 64949               |
|    | <p><b>Racking outlet (page 172)</b></p> <p>› Welded gland with thread NW 50 DIN 11851</p> <p>› With disc valve NW 50 DIN 11851</p>  | 2x KA-120D<br>2x 64945 |
|    | <p><b>Fill level (page 177)</b></p> <p>› Fill level indicator NW 10 mounted</p>   | 2x FS-130H             |
|  | <p><b>Bottom outlet (page 172)</b></p> <p>› With yeast plug</p> <p>› With disc valve NW 50 DIN 11851</p>  | 2x HS-100A<br>2x 64945 |
|  | <p><b>Temperature measurement (page 180)</b></p> <p>› Bi-metal dial thermometer <math>\varnothing</math> 100 mm, measuring range -20 °C to +60 °C</p> <p>› Threaded sleeve with locking screw and cap nut NW 10 DIN 11851</p>   | 2x TM-140C             |
|  | <p><b>Heating and cooling jacket for base tank (page 128)</b></p> <p>› Double jacket C5 1,3m<sup>2</sup> with welded gland G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>  | 1C5                    |
|  | <p><b>Heating and cooling jacket for stacking tank (page 128)</b></p> <p>› Double jacket C5 1,3m<sup>2</sup> with welded gland G 1" for connection to available warm water / cold water source</p> <p>› Version 1, layout 50, connection position C5</p>  | 1C5                    |
|  | <p><b>Adjustable feet (page 184)</b></p> <p>› With adjustable feet for tank legs (H= + approx. 100mm)</p>   | 46126                  |